

BestSet[®] Closet Ring Submittal BS10010 Rev.02-13

Mechanical Closet Ring System

Suggested Spec

All drain, waste, vent, sewer and storm lines shall be of cast iron soil pipe, fittings and couplings, and shall be NSF Certified to conform to the CISPI 301 standard, and shall comply with ASTM A 888, latest edition. Pipe and fittings shall be marked with the collective trademarks of the Cast Iron Soil Pipe Insitute and NSF Interna-

tional, indicate the manufacturer's

name, country of origin, and date of manufacture, or receive prior approval of the engineer.

Date		
Project		
Architect		
Engineer	 	
Contractor		





BestSet [®] With Cap				BestSet [®] Without Cap			
Part No.	Size	Box Qty	Weight	Part No.	Size	Box Qty	Weight
8020	4X2	12	5	8021	4X2	12	5
8023	4X4	8	6	8022	4X4	8	6
8024	4X3	12	5				

BestSet® Closet Rings are cast iron rings developed and manufactured by AB&I Foundry to the CISPI 301 and ASTM A888 standards. The BestSet® features a gasket comprised of neoprene as the primary elastomer and complies with ASTM C-564. The gasket fills the space around the pipe between the pipe and the closet ring, ensuring a water-tight seal. The BestSet® Closet Flange system includes 304 stainless steel bolts.

The BestSet[®] is available with a test cap that reduces man hours during the testing process and ensures that no debris has fallen into the waste line.

Note: Recommended torque during installation is 60ft-lbs

IAPMO File No. 3279

